HWF Phos

HWF Phos is formulated to treat ferrous and non-ferrous substrates prior to painting application. HWF Phos is designed to pre-clean and produce a paint-bonding phosphate coating on ferrous and non-ferrous metals. This coating provides excellent paint adhesion and protects metal surfaces with its exceptional corrosion inhibiting properties. HWF Phos improves the impact resistance and flexibility of applied paint films and prevents the under rusting of paints if the paint film is scored or chipped. It can be applied by brushing, rolling or spraying on metal surfaces from the bottom-up to prevent surface streaking; subsequent rinsing is not required.

Features/Benefits

- Excellent paint adhesion.
- Exceptional corrosion resistant phosphate coating.
- Effectively cleans and improves impact resistance and flexibility of applied paint films.
- Prevents the under-rusting of paints if the paint film is chipped or scarred.
- Rinsing is not required.
- Liquid material for ease of use.

Application

- To apply HWF Phos, ferrous and non-ferrous substrates must be rust- and paint-free.
- Pre-treated articles in contact with moisture, HWF Phos must be re-applied prior to organic coatings.
- To apply organic coatings, pre-treated articles must be dried.

HWF Phos

Operating Conditions

Concentration	Concentrated*
Temperature	Ambient
Time	1 to 4 minutes

*No dilution necessary.

The data and statements contained in this bulletin are based on testing information and are believed to be accurate and reliable. This bulletin is not a Guarantee or Warranty, express or implied regarding the products use. The product is sold on the condition that the purchaser will do their own tests to determine the suitability of the product in a particular application.

READ THE MSDS BEFORE USING THIS PRODUCT