Defoamer 2000

Defoamer 2000 is concentrated silicone-free foam manager used in various aqueous systems. Its stability makes it extremely effective in both acidic and alkaline environments.

Features/Benefits

- 100% active formulation of compounded hydrocarbons.
- Easily dispersible and water dilutable.
- Robust shear stability when properly diluted.
- Does not interfere with turbidity monitors.

Applications

Defoamer 2000 can be utilized in paint and plating lines, water treatment and other application where persistent foam suppression is needed. Used in applications where silicone build-up from other defoamers is a concern.

Operating Conditions

- Stable between pH 3 – 11.
- Agitate product prior to use.
- For optimal dispersion add product with agitation.
- Add product prior to the point where foaming occurs within the system, if possible.
- Concentration of product varies with application. As a guideline, begin trial levels at 0.1% - 0.2% b.v. then work down to the level of foam control desired.

Defoamer 2000 may stratify during storage, gently agitate before use. This product is not damaged by freezing. If stored in cold conditions, warm to room temperature before mixing.

The data and statements contained in this bulletin are based on testing information and are believed to be accurate and reliable. This bulletin is not a Guarantee or Warranty, express or implied regarding the products use. The product is sold on the condition that the purchaser will do their own tests to determine the suitability of the product in a particular application.

READ THE SDS BEFORE USING THIS PRODUCT