ABI Auxiliary Lube

ABI Auxiliary lube is an advanced versatile long-life premium performance lithium-complex soap-thickener used in a multitude of equipment applications. It has been designed to provide outstanding wear protection, adhesion and water resistance, excellent rust and corrosion protection and very good resistance to thermal, oxidative and structural degradation in high temperature applications. It meets the demanding applications in many industries including transportation, manufacturing, construction, mining, logging, and plating equipment in surface finishing applications for flight bars, busses, carriages, saddles, and connections to rectifiers.

Features/Benefits

- Provides superior protection against rust and metal corrosion; readily meeting ASTM D1743 and 24-hour copper corrosion test at 100°C.
- It has good heat stability, significantly extending greasing-interval requirements.
- Extreme pressure resistance and wear protection under severe-shock loading conditions.
- Meets Bucytus Erie multi-purpose grease specification X-2618 for heavy-duty ball and roller bearings. This specification includes a stringent ASTM D2596 requirements for load weld and load wear index.
- It has a broad temperature range, normally for -30°C to +150°C

The data and statements contained in this bulletin are based on testing information and are believed to be accurate and reliable. This bulletin is not a Guarantee or Warranty, express or implied regarding the products use. The product is sold on the condition that the purchaser will do their own tests to determine the suitability of the product in a particular application.
READ THE SDS BEFORE USING THIS PRODUCT

Aqua Bond Inc. PO Box 63635, Toronto, ON, M1V 5K2 Phone: 416-754-7211 w.w.w.aquabond.ca