Guardcoat™ Oil

Guardcoat™ Oil is an emulsifiable, rust preventative oil designed for use over heavy zinc phosphates. Guardcoat™ Oil is formulated to provide maximum corrosion protection and extended service life of the coated surfaces. It offers excellent salt spray resistance to Heavy Zinc phosphated steel for over 120 hours. Guardcoat™ Oil is suited for immersion or spray application. Guardcoat™ Oil produces a transparent, tack free corrosion resistant coating that will not interfere with subsequent processes.

Guardcoat™ Oil can also be used on bare steel and its alloys that are temporarily exposed to humid or corrosive environment. It is ideal for short-term outdoor or long-term indoor storage.

Features/Benefits

- Exceptional emulsifying and rust preventative properties.
- Excellent salt spray resistance to phosphated steel.
- Prevents rusting of steel substrates during transit.
- Provides clear corrosion resistant finishes.
- Dry-to-touch, tack free film.
- Economical single step system.
- Liquid material for ease of use.

Aqua Bond Inc. · PO Box 63635, Toronto, ON M1V 5K2·Tel. 416·754·7211·www.aquabond.ca

Guardcoat™ Oil

Operating Conditions

Concentration	10 to 30 % by volume Guardcoat™ Oil
Temperature	60 to 82 ºC (140 to 180 ºF)

It is recommended for application after machining, cleaning, pickling or phosphating of steel substrates requiring corrosion protection.

To remove the rust preventative coating from bare steel substrates, the use of alkaline cleaners is sufficient.

The data and statements contained in this bulletin are based on testing information and are believed to be accurate and reliable. This bulletin is not a Guarantee or Warranty, express or implied regarding the products use. The product is sold on the condition that the purchaser will do their own tests to determine the suitability of the product in a particular application.

READ THE SDS BEFORE USING THIS PRODUCT

Aqua Bond Inc. · PO Box 63635, Toronto, ON M1V 5K2·Tel. 416·754·7211·www.aquabond.ca